UK CA

FLORIM

DECLARATION OF CONFORMITY

No. **FLORIM 001** UKCA (EN) - Rev. 0

1. Unique identification code of the product type

Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5$ %

2. Intended use(s)

For internal and external walls and floorings

3. Name or registered trade mark, and contact address of the manufacturer

FLORIM CERAMICHE S.p.A. SB,
Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia

4. System(s) of assessment and verification of constancy of performance (AVCP)

System 4

5. Name and identification number of notified laboratory, if relevant – **Not applicable**

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	**$A1_{FL}$/A1**	**Based on the decision 96/603/CE and its changes**
Release of dangerous substance, for:		**BS EN 14411:2012**
- Cadmium	**NPD**	
- Lead	**NPD**	
Breaking strength	**> 1300 N**	
Slipperiness	See table attached	
Tactility	**NPD**	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	**NPD**	
Thermal shock resistance	**Pass**	
Durability for:		
- internal use:	**Pass**	
- external use: freeze-thaw resistance	**Pass**	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of conformity is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

.....
Name and function

Fiorano Modenese, 01/09/2021

.....
Place and date of issue

.....
Signature

Allegato alla Dichiarazione di Prestazione
Attachment to Declaration of Performance
Annexe à la déclaration de performance
Anhang der Leistungserklärung
Anexo a la Declaración de Performance
Załącznik do deklaracji właściwości użytkowych
A Teljesítmény Nyilatkozat kiegészítő táblázata
Bijlage bij de prestatieverklaring
Navezanost na izjave o lastnostih
Aneks Izjave o svojstvima
No. FLORIM 001

Tabella - Scivolosità (dove richiesto dalla legislazione)
Table - Slipperiness (where required by regulation)
Table - Glissement (si requis par la loi)
Tabelle - Rutschsicherheit (wo erforderlich durch die Gesetzgebung)
Tabla - Deslizamiento (donde sea requerido por ley)
Tabela - Poslizgowosc (gdzie wymagane przez prawo)
Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)
Tabel - Antislipwaarde (indien door de wetgever vereist)
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)
Rev. 3 del/of/de/vom/de/a 29.04.2021

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

FLORIMSTONE

Serie / Series / Kolekcja / Serija	CEN/TS 16165:2012 Annex B α_{SHOD}	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
CEMENT velvet 12 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
CEMENT velvet 20 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
COLOR glossy 12 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
COLOR glossy 20 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
COLOR matte 12 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
COLOR matte 20 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
MARBLE glossy 12 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
MARBLE glossy 20 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
MARBLE matte 12 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
MARBLE matte 20 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
METAL matte 12 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
METAL matte 20 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
SOLID glossy 20 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
SOLID matte 20 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
STONE glossy 12 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
STONE matte 12 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
STONE matte 20 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
STONE velvet 12 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
WOOD matte 12 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
WOOD matte 20 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.

CE MARKING

Fine porcelain stoneware
Glazed porcelain stoneware
Coloured body porcelain stoneware

CE	
FLORIM CERAMICHE S.p.A. SB, **Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia** 05 FLORIM 001	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5$ %, for internal and external walls and floorings	
Reaction to fire	$A1_{FL}$/A1
Release of dangerous substances, for:	
- Cadmium	NPD
- Lead	NPD
Breaking strength	> 1300 N
Slipperiness, as:	See table attached
Tactility	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass
https://www.florim.com/en/complete-ce-marking/	