FLORIM

DECLARATION OF PERFORMANCE

No. **FLORIM 003** (EN) - Rev. 1

1. Unique identification code of the product type
   Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5$ %
2. Intended use(s)
   For internal and external walls and floorings
3. Name or registered trade mark, and contact address of the manufacturer
   FLORIM CERAMICHE S.p.A. SB,
   Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia
4. System(s) of assessment and verification of constancy of performance (AVCP)
   System 4
5. Name and identification number of notified laboratory, if relevant – **Not applicable**
   Task(s) carried out
   AVCP system
   Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	**$A1_{FL}$/A1**	**Based on the decision 96/603/CE and its changes**
Release of dangerous substance, for:		**EN 14411:2012**
- Cadmium	**NPD**	
- Lead	**NPD**	
Breaking strength	**> 700 N**	
Slipperiness	See table attached	
Tactility	**NPD**	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	**NPD**	
Thermal shock resistance	**Pass**	
Durability for:		
- internal use:	**Pass**	
- external use: freeze-thaw resistance	**Pass**	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued in accordance with regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.
This declaration is available on the website https://www.florim.com/en/declarations-of-performance-ce/.
Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato
.....
Name and function

Fiorano Modenese, 01/09/2021
.....
Place and date of issue

.....
Signature

Allegato alla Dichiarazione di Prestazione
Attachment to Declaration of Performance
Annexe à la déclaration de performance
Anhang der Leistungserklärung
Anexo a la Declaración de Performance
Załącznik do deklaracji właściwości użytkowych
A Teljesítmény Nyilatkozat kiegészítő táblázata
Bijlage bij de prestatieverklaring
Navezanost na izjave o lastnostih
Aneks Izjave o svojstvima
No. FLORIM 003

Tabella - Scivolosità (dove richiesto dalla legislazione)
Table - Slipperiness (where required by regulation)
Table - Glissement (si requis par la loi)
Tabelle - Rutschsicherheit (wo erforderlich durch die Gesetzgebung)
Tabla - Deslizamiento (donde sea requerido por ley)
Tabela - Poslizgowosc (gdzie wymagane przez prawo)
Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)
Tabel - Antislipwaarde (indien door de wetgever vereist)
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)
Rev. 2 del/of/de/vom/de/a 01.09.2021

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

FLORIMSTONE

Serie / Series / Kolekcja / Serija	CEN/TS 16165:2012 Annex B α_{SHOD}	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
CEMENT matt 6 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
CEMENT velvet 6 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
COLOR glossy 6 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
COLOR matte 6 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
MARBLE glossy 6 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
MARBLE matte 6 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
MARBLE velvet 6 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
METAL matte 6 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
STONE glossy 6 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
STONE matte 6 mm	N.P.D.	>0,4	N.P.D.	N.P.D.
STONE velvet 6 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.
WOOD matte 6 mm	N.P.D.	N.P.D.	N.P.D.	N.P.D.

CE MARKING

Fine porcelain stoneware MAGNUM

CE	
FLORIM CERAMICHE S.p.A. SB, Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia 09 FLORIM 003	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5$ %, for internal and external walls and floorings	
Reaction to fire	$A1_{FL}$/A1
Release of dangerous substances, for:	
- Cadmium	NPD
- Lead	NPD
Breaking strength	> 700 N
Slipperiness, as:	See table attached
Tactility	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass
https://www.florim.com/en/complete-ce-marking/	