



Transform your residential and commercial project with the elegant look of natural wood with the MOOD WOOD collection by Milestone.

Combining a sleek, matte finish with an array of five warm color compositions, MOOD WOOD provides the durability of porcelain tile with the authentic look of wood popular in modern interior design.





CASSETTONE DÉCOR



colors



MOOD WOOD / CASSETTONE DÉCOR #1



MOOD WOOD / CASSETTONE DÉCOR #2



MOOD WOOD / CASSETTONE DÉCOR #3





MOOD WOOD / CASSETTONE DÉCOR #4


The merging of modern, sophisticated wooden tile with the classic, natural look of wood paneling, Cassettone Décor is a new approach to a contemporary taste. Featuring geometric sequences with multiple shades that pay homage to the essence of furnishing items, Cassettone Décor perfectly provides a peaceful, welcoming feel.

Available in one size (24"x24") and 4 color combinations, the Cassettone Décor can be used by itself or combine with anyone of the 5 colors of Mood

Wood Collection.







MOOD WOOD / WHITE







6"x36". 8"x48" / WHITE . cassettone Décor 1 24"x24"






















MOOD WOOD / HONEY





































MOOD WOOD / GREY












38 MOOD WOOD














MOOD WOOD / NUT

42 MOOD WOOD











MOOD WOOD / BROWN

46 MOOD WOOD





SIZES & SHADE VARIATION

48

sizes:

6"x36"

Rectified / Matte

1100803 White

1100804 Honey

1100805 Nut

1100806 Brown 1100807 Grey 8"x48"
Rectified / Matte

1100788 White

1100789 Honey

1100790 Nut

1100791 Brown

1100792 Grey

24"X24" CASSETTONE DÉCOR Rectified / Matte



1100839 White / Grey Cassettone Décor 1



1100840 Honey / Nut Cassettone Décor 2



1100841 Honey / Nut / Brown Cassettone Décor 3



1100845 Nut/ Brown Cassettone Décor 4

OUTDOOR #2

12"x48" Rectified / Matte

1100818 White 1100819 Honey 1100822 Grey

Colors shown may vary from actual product. Final selection should be made from actual product samples.

mosaics & trim pieces:

12"x15" Herringbone Mosaic Matte



- 1100828 White
- 1100829 Honey
- 1100830 Nut
- 1100831 Brown
- 1100832 Grey

3"x36" Bullnose / Matte



- 1100823 White
- 1100824 Honey
- 1100825 Nut
- 1100826 Brown
- 1100827 Grey




UNIFORM APPEARANCE

Differences among pieces from the same production run are minimal.



SLIGHT VARIATION Clearly distinguishable differences in texture and/or pattern with similar colors.



While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece will vary significantly.



SUBSTANTIAL VARIATION

Random color differences from tile to tile, so that one tile may have totally different colors from that on other tiles. Thus, the final installation will be unique.

CASSETTONE DÉCOR





Technical Specifications

This product meets or exceeds all standards described in ANSI A137.1 & A137.3. Este product cumple o exceed todos los estandares de ANSI A137.1 & A137.3.

	SPECS	TEST METHOD	INDUSTRY STANDARD	MILE®stone VALUES	
	WATER ABSORPTION	ASTM C373	≤0.5%	≤0.5%	
*	SURFACE WEAR RESISTANCE	ANSI A137.1	Surface Wear-resistance properties of glazed vitreous and porcelain tiles.	ALL RESIDENTIAL / COMMERCIAL	
•	CHEMICAL RESISTANCE	ASTM C650	A tile sample is placed in continuous contact with a variety of chemicals for 24 hours. Sample must show no visible defects.	NOT AFFECTED	
*	D.C.O.F. AcuTest®	ANSI A326.3	INDOOR ≥0.42 WET	≥0.42 WET	
			OUTDOOR >0.55 WET	>0.55 WET 2CM & GRIP	
*	STAIN RESISTANCE	ASTM C1378	Surfaces are exposed to staining agents for 24 hours followed by four cleaning procedures. Results are recorded post cleaning.	NOT AFFECTED	
	BREAKING STRENGTH GAUGED PORCELAIN	ASTM C1505	≥175 lbf	≥200	lbf
<u>Å</u>	BREAKING STRENGTH	ASTM C648	≥275 lbf	≥300 lbf	
	BREAKING STRENGTH OUTDOOR 2CM	ASTM 1505	2000 lbf (10.9 kN)	≥2500) lbf
*	RESISTANCE TO FREEZE	ASTM C1026	A tile sample is subjected to repeated processes of freezing and thawing. Sample must show no visible defects.	RESISTANT	
	WARPAGE EDGE	ASTM C485	±0.40% or ±0.05 in (±1.8 mm)	± 0.40%	Rectified
	WARPAGE DIAGONAL	ASTM C485	±0.40% or ±0.07 in (±1.8 mm)	± 0.40%	Rectified
Н	WEDGING	ASTM C502	±0.25% or ±0.03 in (±0.8 mm)	± 0.25%	Rectified
	WARPAGE EDGE	ASTM C485	±0.50% or ±0.07 in (±1.8 mm)	± 0.50%	Calibrated
	WARPAGE DIAGONAL	ASTM C485	±0.50% or ±0.07 in (±1.8 mm)	± 0.50%	Calibrated
H	WEDGING	ASTM C502	±0.50% or ±0.08 in (±2.0 mm)	± 0.50%	Calibrated
<u> </u>	THICKNESS	ASTM C499	Range: ± 0.04 in	≤0.04 in	

[•] Due to the inherent nature of fired porcelain tile, it is important to note that the coefficent of friction may vary within and between product runs.

Cleaning & Maintenance / Routine Care Instructions



Scan the QR code with your smartphone.

Green Memberships & Accreditations

DESCRIPTION

	DESCRIPTION
Red List Free Declare.	Declare labels disclose all intentionally added ingredients and residuals present in the final product. Being Red List Free means the worst materials, chemicals, and elements for human and environmental health are not present within our products.
hpd VERSION 2.0	The Health Product Declaration Collaborative transparency declaration for all of Florim USA's naturally occurring materials.
EPD®	Certification of plant and product specific Environmental Product Declaration (EPD) which tracks environmental impacts from the production of porcelain tile.
G GREEN SQUARED	Tile Council of North America and the American National Standards Institute's standard for sustainability and environmental impact.
GREENGUARD PROVIDENT PROVIDENCE TO COMPANY COLD	Underwriter's Laboratories certification of low emitting materials. Florim USA is Green Guard Gold certified.
Secretario de Constituto de Co	Defines post-consumer content of as much as 3% recycled material which reduces landfill impact. Certified by Bureau Veritas.
Consume The Recorded Control	Defines pre-consumer content of as much as 45% recycled material which reduces our carbon footprint. Certified by Bureau Veritas.
INTERNATIONAL LIVING FUTURE INSTITUTE	Florim USA's sustainability and social practices support the mission of The International Living Future Institute which strives to create a socially just, culturally rich, and ecologically restorative community.
TEMBER PROPERTY OF THE PROPERT	USGBC is committed to suit a more sustainable life. Florim USA supports this mission by manufacturing products which aid architects in achieving USGBC certification.
	Florim USA sources >95% raw material within a 500 mile radius, which results in a smaller carbon footprint.
TILE COUNCIL OF NORTH AMERICA, INC.	Florim USA actively participates in the Tile Council of North America which allows us to be on the forefront of advances in the tile industry and its standards.
* X	The Tennessee Recycling Coalition is dedicated to promoting recycling and sustainable material management practices, and awarded Florim USA the Tennessee Recycler of the Year award for 2020.
ESO 9001 Outley morest Outley CERTIFED ISO 14001 Environment Southern CERTIFED CERTIFED CERTIFED	ISO 9001 & ISO 14001 are globally recognized standards. ISO 9001 certifies that Florim USA products and practices continually meet and exceed customer and regulatory requirements. ISO 14001 certifies that Florim USA complies with environmental regulations and that it's manufacturing practices are environmentally conscious.
BENEFIT CORPORATION	Florim USA updated its corporate charter in 2022 to become a Benefit Corporation. Our company is committed to maintaining this designation through initiatives focused on sustainability, social responsibility, ethical business practices and transparent, annual reporting on our social and environmental performance.

Progress that invests in the entire society

As an active member of the U.S Green Building Council, MILE*stone spreads awareness to the community and encourages the use of building solutions through environmentally friendly practices.

Our products positively contribute to the requirements for obtaining the LEED (Leadership in Energy and Environmental Design) and WELL (IWBI) certifications.

A commitment to environmental sustainability and responsibility

We are committed to conscious development that minimizes the negative impact of manufacturing production on the environment. Our general approach to sustainability intersects with our business strategy to embrace three areas of responsibility: economic, social, and environmental. Some ways we prove this are:

- Products containing as much as 45% recycled content.
- Post-consumer recycled content levels as much as 3%.
- Zero industrial wastewater discharge.
- A 99% internal process recycling rate.
- Local sourcing of >95% raw materials (within 500-mile radius of factory) resulting in low transportation related carbon emissions.

MILE*stone is taking these and other steps, as well as actively investing to reduce carbon emissions to ensure that we reach full carbon neutrality.





300 International Blvd. Clarksville, TN 37040 | www.milestonetiles.com | 1-877-356-7461

